

November 08, 2023

Basic Training for Saturn

Star Charge Europe GmbH

Ruo Yi, Technical Support Engineer

Table of Contents

Brief Introduction

Installation

Commissioning



Brief Introduction

Specification



[1] — 4.3-inch display screen

[2] — RFID reader

[3] — AC meter

[4] — Nameplate

[5] — Charging socket

[6] — Sealed casings at power cable inlets

[7] — Network cable interface

[8] — LED status lights



General Information	
Charging Mode	Mode 3 (IEC 61851-1)
Input/Output Power&Current Rating	2 x 22kW/2 x 32A max.
Input/Output Voltage Rating	400Vac±10%, 2*3 phases, 50/60Hz, L1+L2+L3+N+PE
Grid Type	TN-S, TN-C, TN-C-S, TT
Charging Interface	Configuration 01: 2 x IEC 62196-2 Type 2 tethered plug (Case C) Configuration 02: 2 x IEC 62196-2 Type 2 socket (Case B)
Metering	MID meter, Accuracy: Class 1
Internal RCD	Type B
Protection	Overcurrent, Overvoltage, Undervoltage, Residual current, Short circuit, Over temperature, Ground fault, Integrated surge protection
Mechanical	
IP Rating	IP54@Case B, IP55@Case C
IK Rating	IK10
Cooling	Natural cooling
Charging Cable Length	5m
Dimensions (WxHxD)	395*504*197mm
Weight	Approx. 11kg (Case B) Approx.16kg (Case C)
Installation	Wall mounting, Pole mounting (Pole is optional)
Certification and standards	
Standards and compliance	IEC 61851-1, IEC 61851-21-2, LVD 2014/35/EU, RED 2014/53/EU
Certification	CE





Installation

Requirements & Workflow



Installation - Requirements

1.Requirements for grid capacity

- AC working voltage: AC 400V \pm 10%
- AC working frequency: 50Hz/60Hz
- It is recommended that customers install a miniature circuit breaker upstream to Saturn.

The recommended specifications of the circuit breaker are as follow


Power	Series	Rated Voltage	Rated Current	Tripping Characteristics	Quantity
22KW	3P+N	400V	40A	B/C	1
22KW + 22KW	3P+N	400V	40A	B/C	2




2. Installation foundation

The charger shall be installed on a hard mounting floor (e.g. cement floor), if there is no appropriate mounting floor on site, a concrete foundation is recommended.

- Size 500mm * 350mm * 600mm
- Depth of the foundation 400mm
- Height above the ground 200mm.
- The foundation is filled with C20 concrete



2. Installation foundation



3. Power cable specification

- 5 * 6mm² (L1,L2,L3,N, PE)
- The core material is copper.






Installation Workflow Wall Mounted



Installation Workflow – Wall Mounted




- 1-Front cover;
- 2-Charging station;
- 3- M6*60 expansion screw;
- 4-Mounting bracket;
- 5-M6*16 hexagon socket screw;
- 6-M4*8 hexagon socket screw.



Installation Workflow – Wall Mounted

Step 1:



Please confirm the installation location and mark it on the wall. It is suggested that the top height of charging pile should be about 1 - 1.45 meter from the ground



Installation Workflow – Wall Mounted

Step 2:



Place the template at a suitable height, and mark the punching position on the wall with a pencil




Installation Workflow – Wall Mounted

Step 3:

- Use a $\Phi 10$ drill bit to drill 4 holes with depth of 80mm.
- Use two M6*60 screws to fasten the wall mount to the holes at the bottom
- Insert two M6*60 screws in the holes at the top. Note that the screw head protruding length is 7mm.






The screw head protruding length is 7mm



Installation Workflow – Wall Mounted

Step 4:




- First move one screw at the bottom of front cover, then remove the front cover with a card and the cable cover
- Loosen the two clamp screws of inlet cable



Installation Workflow – Wall Mounted

Step 5:



- Thread two input cable through the two waterproof glands
- Connect power line according to the marker. Screw torque is 1.4-1.6Nm



Installation Workflow – Wall Mounted

Step 6:


- Fasten the clamp screws and lock the inlet cable. Screw torque is 1.4-1.6Nm
- Optional: If Ethernet cable is required, you can thread the Ethernet cable through the small gland and connect it to the internal network cable interface.



Installation Workflow – Wall Mounted

Step 6:




- Optional: If SIM card is required, Insert the SIM card into the SIM card slot.



Installation Workflow – Wall Mounted

Step 7:

- Install the cable cover back to the charger
- Install the front cover






Installation Workflow – Wall Mounted

Step 8:

- Hang the on the wall
- Fix the charger to the wall by using two M6*16 screws






Installation Workflow Column Mounted




Installation Workflow – Column Mounted



Installation Workflow – Column Mounted

Step 1:


- Lay the column flat on the ground and pass the incoming line out from the front.



Installation Workflow – Column Mounted

Step 2:


- Erect the column and fix it to the foundation with 4 M4*120.



Installation Workflow – Column Mounted

Step 3:




- Add the decorative cover to the pedestal ..



Installation Workflow – Column Mounted

Step 4:

- Hang the charger body to the column and fix it at the bottom with 2 M6 screws.
- After that, connect the power cables to charger .








Commissioning

Tools & Workflow



Commissioning - Tools


Item	Tools	Usage	Example
1	Laptop	Configure the settings, read the log, Troubleshooting	
2	Ethernet cable	Connect laptop to charger	
3	Screwdriver set	Assemble and disassemble the screws	



Commissioning - Workflow

1. Connect laptop to charger

- Connect your laptop with the charger via Ethernet cable.
- To access the charger system, you need to set the IP address of your laptop to 192.168.88.200 and subnet mask to 255.255.255.0



2. Log into charger web panel

- Open an internet browser (Google chrome)
- Enter in website address 192.168.88.206
- Log in:

Normal account:


Username : xxcd

Password : 28912891

Advanced account:

Username : wbdh

Password : 26835941



Commissioning - Workflow

3. Parameter configuration

Software settings needs to be configured:

- Internet communication (4G, Ethernet, WIFI)
- OCPP backend
- Charger authentication method
- Output power configuration


Login

Username

Password

Sign me in

3. Parameter configuration



Collection of the most used settings

Charger connector settings for connector type, output power limit, etc.

Settings for 4G, Ethernet, WIFI, OCPP and authentication methods

Check the internet and backend connection status

Firmware update and log download




3. Parameter configuration

Firmware update

In the first commissioning of a new charger, the firmware of the charger is usually relative old and needs to be updated to newest version to optimize the charger performance.

To check the firmware version, go to “Software setting ” and find “version” data.

Star Charge engineer will provide you the newest firmware version and guide you do the update.



The screenshot shows a web interface for 'Software Setting'. On the left is a dark sidebar with a menu containing 'Hardware Setting', 'Software Setting' (highlighted in orange), 'Charging Status', and 'Upload and download'. The main content area has a title 'Functions Enable' with a subtitle '(Get data error)'. Below this are four dropdown menus: 'Card Type' (set to 'Billing card'), 'Whether to open the qr code process' (set to 'No'), 'Local startup whether to go ocpp background' (set to 'No'), and 'Whether to transfer private data' (set to 'No'). A 'PM' button is visible. The next section is 'Time Zone And DST Setting' with an 'Enable modification' checkbox. Below that is 'UTC Time Setting' showing 'Similar to 2019-07-01 08:45:45' and a timestamp '2022-11-01 11:16:49'. The final section is 'Get version', which contains a 'Version' label and a text input field displaying '1.5.1.8.1b213'. A red arrow points from the 'Software Setting' menu item to this 'Get version' section. A 'RY' button is at the bottom right of the interface.



3. Parameter configuration

Firmware update


- Go to “Upload and download”
- Click “Brows” under “UBI firmware upload”
- Assign the firmware file “firmware.zip”
- Click “Submit” . A message “success” will pop up after the firmware is uploaded to charger. After that the charger will begin the upgrading process, it will take 5 minutes.



3. Parameter configuration

Internet communication (4G, Ethernet, Wifi)

1. Click “Enable modification”
2. Enter data for APN, User, Psw and Pin
3. Click “Submit”




The screenshot displays the Star Charge web interface. On the left is a dark sidebar with navigation links: Quick Setup, Hardware Setting, Software Setting (highlighted in orange), Charging Status, and Upload and download. The top header is dark with the Star Charge logo, a Language dropdown, and a User Set dropdown. The main content area has a light background. At the top of this area are 'Submit' and 'Refresh' buttons. Below is the '4G configuration' section, which contains a red-bordered box. Inside this box, the 'Enable modification' checkbox is checked. Below it are four input fields labeled APN, User, Psw, and Pin. Under the APN field is an 'EncryptType' dropdown menu showing 'A'. Below the red box are 'Submit' and 'Refresh' buttons, with the 'Submit' button highlighted by a red box. Below the 4G configuration is the 'Ethernet configuration' section, which has an unchecked 'Enable modification' checkbox and 'Submit' and 'Refresh' buttons. At the bottom, the 'DNS configuration' section is partially visible.



3. Parameter configuration

OCPP backend

Set CP backend: Enter data for URL, Path, Port and SSL_ON according to OCPP backend address



The screenshot shows the StarCharge web interface for OCPP configuration. The left sidebar contains navigation links: Home, Software Configuration, CP Configuration, CP Status, Power Unit Configuration, Power Unit Status, SmartOPS, and Upload And Download. The main content area is titled 'OCPP' and 'CP Backend'. It contains several input fields: URL (36.153.57.202), Path (/steve/websocket/CentralSystemServi), Port (3400), and SSL_ON (0). There is also an Authorization key field. To the right of these fields are 'Submit' and 'Refresh' buttons. Below this is a 'Certificate import' section with a file input and a 'Brows' button, followed by a 'Submit' button. The 'Additional Function' section includes dropdowns for Authentication (Card Not Authentication), QR-Code Process (No), Interaction With Backend For All (No), and Private Data (No), with 'Submit' and 'Refresh' buttons. The 'Time Zone And DST Setting' section has fields for Time Zone and DST Enable.



3. Parameter configuration

OCPP backend

Take `http://36.153.57.202:3400/steve/websocket/CentralSystemService` as an example. The information need to be filled in is shown as below:

Star Charge

Language User Set

Home

Software Configuration

CP Configuration

CP Status

Power Unit Configuration

Power Unit Status

SmartOPS

Upload And Download

OCPP

CP Backend

URL: 36.153.57.202 Path: /steve/websocket/CentralSystemServi

Port: 3400 SSL_ON: 0

Authorization key:

Submit Refresh

Certificate import

Brows

Submit

Additional Function

Authentication: Card Not Authentication

QR-Code Process: No

Interaction With Backend For All: No

Private Data: No

Submit Refresh

Time Zone And DST Setting

Time Zone: DST Enable:




3. Parameter configuration

OCPP backend

Set CP Identity: Enter the charger ID number which is registered in the OCPP backend.

EVSE ID: Please ensure the parameter is "1-1"



The screenshot shows the 'Star Charge' web interface. On the left is a dark sidebar with navigation links: 'Quick Setup', 'Hardware Setting' (highlighted in orange), 'Software Setting', 'Charging Status', and 'Upload and download'. The main content area is titled 'Hardware Setting' and includes a breadcrumb trail 'Home / Setting / Hardware Setting'. Below this is the 'Identification' section, which contains two input fields: 'ChargePoint Id' with the value '1234' and 'Group Number' with the value '1234'. Below these is the 'Evse Id' field, which has a note '(Please submit any changes immediately)' and the value '1'. Two large red arrows point to the 'ChargePoint Id' and 'Evse Id' fields respectively, highlighting the configuration steps mentioned in the text.



3. Parameter configuration

Charger authentication method

Following authentication method can be selected:

The screenshot displays the 'Contents' sidebar on the left with 'Software Configuration' highlighted. The main area shows the 'Additional Function' section. The 'Authentication' dropdown menu is open, showing the following options: Local Authentication (selected), Backend Authentication, Local PnC, and AutoCharge. The 'Data Transfer For Mac' dropdown is set to 'Disable'. The 'Submit' button is highlighted with a red box. The 'Refresh' button is also visible next to it.

Contents

Quick Setup

Software Configuration

CP Configuration

CP Status

Power Unit Configuration

Power Unit Status

SmartOPS

Upload And Download

Additional Function

Authentication

Local Authentication

Backend Authentication

Local PnC

AutoCharge

Data Transfer For Mac

Data Transfer For Mac

Disable

Submit

Refresh

Time Zone And DST Setting

☐ Enable modification



3.Parameter configuration

Charger authentication method

Authentication method	Principle
Card Authentication	Use authenticated IC card to start charging session card. The IC card must be whitelisted in backend platform and EVSE must always connect to the backend
Card Not Authentication	Use the IC cards from charger accessories to start charging session. No authentication.
Local PnC	Once plug in the charger connector, the charging session automatically begins without any authentication.
AutoCharge	Similar to PnC mode, but with MAC code authentication. The MAC Code of the EV must be registered in backend.




3. Parameter configuration

Connector and Output power configuration

According to the use scenarios and grid capacity, output power of AC connector can be individually configured .

For example:

- 3200 (default) is for 22kW power
- 1600 is for 11 power



4. Charging test

Starting the session



Ending the session



4. Charging test

LED status indicator



Standby mode for Charging



1. Constant - Cable connected
2. Flashes Quickly - Reading the RFID card
3. Breathing slowly - Charging in session




Error



5. Customer Training and finishing commissioning report

- After the commissioning work for the EVSE, engineer should give a basic training related to the main characteristics of the EVSE to guide the customer how to use EVSE. The training content should cover safety knowledge, basic charging procedure etc.
- Last and not least, the commissioning report needs to be finished after whole work.





Thank You.

Connect the World. Connect the People.



Headquarter: No. 39 Longhui Road, Wujin High-tech Zone, Changzhou, Jiangsu, China
China Office: Building 5, Innovation and Research Port, Changzhou, Jiangsu, China
Europe Office: Rugbyring 12, 65428 Rüsselsheim, Germany
APAC Office: 2 Kung Chong Road, #05-01 AA Centre, Singapore 159140
America Office: 46571 Fremont Blvd, Fremont, CA 94538

www.starcharge.com